Duct - Unitube cables

UNITUBE CABLE 1X12SM SP1647

Aginode Ref: 10231297





This unitube cable is used in the Access, Distribution, City Network and FTTx applications; it is designed to be easily installed in outdoor installations.

Characteristics & Applications

- Easy installation due to the friction properties of the outer sheath
- Robust design
- Waterproof structure
- Halogen free

Fibre type

The cable is available with different fibre types.

Construction

- Jelly filled tube
- Reinforcement elements
- Low friction outer sheath

STANDARDS

IEC 60794

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Unitube Cable 1x12SM SP1647

Characteristics

结构特性	
颜色	黑
光纤类型	SM (G.652D)
铠装类型	玻璃纤维丝
外护套	HDPE
结构类型	Unitube
绝缘	是
尺寸特性	
管数	1
近似重量	40 kg/km
光纤数	12
标称外径	6.9 mm
机械特性	
允许牵引负载	180 daN
使用特性	
操作温度，范围	-30...70 °C
存储温度范围	-40...70 °C
安装类型	户外 - 管道
Installation temperature, range	0...40 °C
敷设时弯曲系数	20 (xD)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.