

# Aerial Metallic Self Supported ULW

## ULW 4X12 SP1922 RR (PIA)

This cable is used for Access, Distribution, City Network and FTTx applications. It is designed for installation in the BT Fibre Network in Overhead and Underground environments.

The cable is design to respond to the British Telecommunications Specifications CW1842 and related specifications CW1500 part 2, 7 and 11.

Maximum spans 68m.

### Characteristics & Applications

- Rodent-repellent outersheath (RR)
- Metallic brass coated rods armouring
- Microbundles inside - easy to open without special tools
- Waterproof dry core structure
- Small size design to minimize the effect of ice and wind
- Fully compatible with the reference BT toolings for cable opening

### Fibre Type

Compliant with BT CW1505 Cat2 and ITU-T G657A1

### Construction

- Jelly filled microbundles containing coloured fibres
- Swellable yarns
- Rodent repellent (RR) HDPE outer sheath with embedded metallic wires
- Colour : Black outer sheath with 2 yellow stripes at 180°

### MARKING in accordance with BT specification CW1402

:

(LASER+PHONE) FB NEXANS COF215 ULTRA LIGHT WEIGHT OH FIBRE CABLE 48F (LASER+PHONE) RR N°OF CCCCCM



### STANDARDS

Customer specification  
IEC 60793  
IEC 60794

# ULW 4x12 SP1922 RR (PIA)

## Characteristics

### 结构特性

光纤类型	SM
外护套	HDPE - UV / Anti-Rodent
不含金属	No
加强构件	Steel rods
结构类型	多束管

### 尺寸特性

管数	4
近似重量	34 kg/km
光纤数	48
标称外径	7.0 mm

### 机械特性

允许牵引负载	65 daN
耐冲击 (EN 187 000)	10 J
耐挤压 (IEC 794-1-E3)	200 N/cm

### 使用特性

防啮齿保护	是
操作温度, 范围	-20...70 °C
存储温度范围	-40...70 °C
安装类型	架空 - 自承式
环境安装温度, 范围	0...40 °C
敷设时弯曲系数	20 (xD)

## 文件

Tableau de charge aérien ULW\_3.xlsx xlsx — 12.17 KB [下载](#) ↓

## 销售和交付信息

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LASER <714> FB WWYY COF215 ULTRA LIGHT WEIGHT OH FIBRE CABLE XXF/21 PROPERTY OF BT - LASER- <714> N°OF - T hor -  
CCCCCM

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*