

LANmark-OF MPO-4DLC扇出光缆LSZH

LANMARK-OF MPO-4DLC FAN-OUT PATCH CORD, SM OS2,LSZH, YELLOW, LOW LOSS, 2M

Aginode Ref: N127.4BLAY2

- Aginode MPO patch cord adopts a slim cable design
- The optical performance of Aginode MPO connector is better than industry level and can meet international standards.
- Available for Bending insensitive Singlemode fiber
- Female MPO connectors one side and Duplex Uniboot LC one side.

Application

Aginode MPO-4DLC fan-out patch cords is designed to support aggregation applications like 40G, 100G and future applications like 400G. Aginode' low loss optical performance can support at least 6 MPO connection to allow intermediate distributors in mega Datacenters. The MPO cable is optimized for OD and remain good pulling force and crush performance.

- MPO connectors met IEC 61754-7-1 and GR-1435-CORE standards
- MPO connector for Singlemode is APC
- OF cable met IEC 60794 standards
- LC connector adopt Uniboot design to provide better fan-out management
- The cable is LSZH material and met IEC 60332-1& IEC 60332-3-24, IEC 61034-2 and IEC 60754-1&2
- MPO Insertion Loss: Max 0.5dB and Typical 0.35dB for SM
- DLC Insertion Loss: Max 0.25dB and Typical 0.15dB for SM



STANDARDS

ANSI/TIA-568-C.3
ISO/IEC 11801

LANmark-OF MPO-4DLC fan-out patch cord, SM OS2,LSZH, Yellow, Low loss, 2m

Characteristics

结构特性

光纤类型	SM (G657.A1)
------	--------------

尺寸特性

外径	3 mm
----	------

机械特性

最大拉力	100 N
------	-------

使用特性

操作温度, 范围	-10...60 °C
----------	-------------

阻燃 - 火焰	IEC 60332-1; IEC 60332-3
---------	--------------------------

存储温度范围	-40...70 °C
--------	-------------