
Microduct - Unitube cables

MICROCABLE 1X24SM 200MM SP2015

Aginode Ref: SP2015

This unitube cable is used in the Access, Distribution, City Network and FTTx applications; it is designed to be easily installed designed for outdoor installation by blowing in microduct.



STANDARDS

EN 187000
IEC 60794

Characteristics & Applications

- High blowing distance due to the excellent friction properties of the outer sheath
- Right balance between flexibility and rigidity
- Aramid yarns reinforcement
- All dielectric design
- Waterproof structure

Construction

- Jelly filled dual wall tube
- Aramid yarns
- Low coefficient of friction sheath

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Microcable 1x24SM 200µm SP2015

Characteristics

结构特性	
颜色	黑
光纤类型	G657A1 - 200 µm
铠装类型	芳纶
外护套	PE-HD
不含金属	Yes
结构类型	Unitube
尺寸特性	
管数	1
近似重量	6 kg/km
光纤数	24
标称外径	2.5 mm
机械特性	
操作时最大拉力负载	10.0 daN
允许牵引负载	15 daN
耐挤压 (IEC 794-1-E3)	100 N/cm
使用特性	
操作温度，范围	-20...70 °C
存储温度范围	-40...70 °C
安装类型	户外 - 可吹缆的微管
Installation temperature, range	0...40 °C
敷设时弯曲系数	20 (xD)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.