

Distribution - Unitube cables Cca

UG LSZH 12XG657A1 SP1975 BK+2LOR(SUN/SW)

Aginode Ref: 10570523

This unitube cable is designed for indoor/outdoor installation.

This cable has an outstanding fire behaviour.

This cable can be operated under a large temperature range.

Design

This UG cable has a central tube with 12 fibres inside . The design is reinforced by a layer of glass yarns and a LSZH* sheath.

Technical performances

The unitube cable performances are specified in the following tables.

Additional details

* LSZH: Low Smoke Zero Halogen.



STANDARDS

EN 50399 B2

IEC 60332-1

IEC 60332-3

IEC 60754-1

IEC 60794

IEC 61034

NF C32-070/C2

UG LSZH 12xG657A1 SP1975 BK+2LOR(SUN/SW)

Characteristics

结构特性

颜色	黑
光纤类型	SM (G657.A1)
外护套	低烟无卤
无卤	IEC 60754-1
长度水密封性所用材料	膨胀纱
不含金属	Yes
加强构件	FRP
结构类型	Unitube
额外加强件	玻璃纱

尺寸特性

近似重量	148 kg/km
光纤数	12
标称外径	11.6 mm

机械特性

机械耐冲击性能	3次冲击/ N.M
耐挤压 (IEC 794-1-E3)	300 N/cm
最大安装拉力	9000 N

使用特性

操作温度, 范围	-30...60 °C
最小弯曲半径 - 静态	150 mm
阻燃 - 火焰	IEC 60332-1
抗UV	是
存储温度范围	-40...70 °C
敷设操作弯曲半径	200 mm
安装类型	室内/户外
Installation temperature, range	0...40 °C
防水	纵向和径向

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

业绩声明

UG LSZH 12xG657A1 SP1975 BK+2LOR(SUN/SW) pdf — 120.35 KB 下载 ↓

销售和交付信息

MARKING : Sunrise Tel. 0800303300 12FS Aginode YYYY N°OF B2ca-s1a,d0,a1 ccccc m

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.