

LANmark-OF 即插即用 MPO 无导针 -LC 模块

LANMARK-OF 即插即用 低损耗模块MPO无导针-双工LC 通用线序 24芯 OM4 水绿色

Aginode Ref: N441.5M24LC4VFU

- 带 24 个 LC 连接的 Play&Play 模块
- 提供 LANmark-OF OM4 多模版本
- 多模低损耗光学性能：0.5 dB 插入损耗
- 通用布线
- 模块可轻松安装到安捷诺的即插即用配线架中
- 高密度：1U 可安装 4 个模块
- 即插即用模块已预先安装，并经过 100% 出厂测试

??? Plug&Play ????? MPO ????? 12 ????? MPO-MPO ?????
???????????????? LC ?????
???? 4 ? Plug&Play ????? Plug&Play ????? 4 ????? 1U ??? 48
LC ????? 96 LC ?????
Plug&Play ????? IEC 61300-3-45 ?????MPO ????? IEC
61300-3-6 ?????

模块为通用线序。
???? TIA-568.3-D????B????????????????????
???????????????? MPO-MPO ?????????

由于所有连接都已在工厂端接并经过测试，因此安装时间很短，便于快速部署。



All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF 即插即用 低损耗模块MPO无导针-双工LC 通用线序

24芯 OM4 水绿色

Characteristics

结构特性		
连接器类型		LC
光纤类型		多模 50/125
尺寸特性		
光纤数		24
传输特性		
最大插入损耗, dB		0.5 dB
插入损耗, 典型值		0.35 dB
最小回波损耗, dB		20 dB

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

