

LANmark-OF MPO-MPO 跳线 LSZH

LANMARK-OF MPO-MPO PATCH CORD, OS2 APC, G.657.A1, STRAIGHT, MPO FEMALE-MPO FEMALE, 12CORE, OFNP, YELLOW, ULTRA LOW LOSS, XM

Aginode Ref: N125.4SUYxNP

- The optical performance of Aginode MPO connector is better than industry level and can meet international standards
- Ultra low loss 0.35dB
- Available for Single Mode
- Straight polarity (Type B) according to TIA 568.3-D
- Female MPO connectors both end

Application

Aginode MPO patch cords is designed to support Datacenter high speed network applications like 40G, 100G, 200G and 400G. Aginode' low loss optical performance can support at least 6 MPO connection to allow intermediatedistributors in mega Datacenters. The MPO cable is optimized for OD and remain good pulling force and crush performance. Each MPO patch cord is delivered with test report by factory to ensure performance.

- MPO connectors met IEC 61754-7-1 and GR-1435-CORE standards
- MPO connector for Singlemode is APC
- OF cable met IEC 60794 standards
- The cable is LSZH material and met IEC 60332-1& IEC 60332-3-24, IEC 61034-2 and IEC 60754-1&2
- Fibre can met IEC 60793-2-50 (B6_a1) and ITU-T G.657.A1 for Singlemode



STANDARDS

ANSI/TIA-568-C.3
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF MPO-MPO patch cord, OS2 APC, G.657.A1, Straight, MPO Female-MPO female, 12core, OFNP, Yellow, Ultra Low loss, xm

Characteristics

结构特性

光纤类型

OS2

传输特性

最大插入损耗, dB

0.35 dB