

# Outlets: @XS-Fast

## OUTLETS: @XS-FAST

### Aginode Ref: TBD

- Up to 2 SC/LC adapters
- Wall mounted, on flush box, on a DIN rail and on most of the electrical equipment mounting supports on the market
- No lid-opening to fix the outlet
- Ready-to-fix kit in option

### Application

By default, it is designed for flush wall mounting. It can also be adapted for use with DIN rails and most standard electrical mounting systems available on the market by means of an optional adapter plate. The @XS-FAST can additionally serve as a DTIO, acting as the termination point of the operator's access network.

### Functional characteristics

The OTO can be installed with a pre-connected drop cable entering from either side, the bottom, or the rear. It features a dedicated splicing area and fibre management zone, enabling cable-to-cable or cable-to-pigtails splicing.



## STANDARDS

Aginode specification

# Outlets: @XS-FAST

## Characteristics

### 结构特性

颜色	白 RAL 9010
材料	Thermoplastic

### 尺寸特性

深度	18 mm
高度	80 mm
最大的适配器数	2
接头数量	2
宽度	80 mm

### 机械特性

IK Rating	5
-----------	---

### 使用特性

适配器	SC/LC
耐火	UL 94 V0
最小弯曲半径 - 静态	15 mm
操作温度, 范围	-5...45 °C
包装	Paper bag
抗UV	是
防水	IP 50

ABS 1594 -FAST PTO.pdf pdf — 981.89 KB [下载](#) ↓