
Outlets: @XS-FAST

OUTLETS: @XS-FAST

Aginode Ref: TBD

- Up to 2 SC/LC adapters
- Wall mounted, on flush box, on a DIN rail and on most of the electrical equipment mounting supports on the market
- No lid-opening to fix the outlet
- Ready-to-fix kit in option



Application

By default, it is designed for flush wall mounting. It can also be adapted for use with DIN rails and most standard electrical mounting systems available on the market by means of an optional adapter plate. The @XS-FAST can additionally serve as a DTIO, acting as the termination point of the operator's access network.

STANDARDS

Aginode specification

Functional characteristics

The OTO can be installed with a pre-connected drop cable entering from either side, the bottom, or the rear. It features a dedicated splicing area and fibre management zone, enabling cable-to-cable or cable-to-pigtails splicing.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Outlets: @XS-FAST

Characteristics

结构特性	
颜色	白 RAL 9010
材料	Thermoplastic
尺寸特性	
深度	18 mm
高度	80 mm
最大的适配器数	2
接头数量	2
宽度	80 m
机械特性	
IK Rating	5
使用特性	
适配器	SC/LC
耐火	UL 94 V0
最小弯曲半径 - 静态	15 mm
操作温度，范围	-5...45 °C
包装	Paper bag
抗UV	是
防水	IP 50

Notice @XS-OUTLET FAST.pdf pdf — 5.26 MB 下载

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.