

UPSKY™ preterminated cable singlemode & multimode

UPSKY™ PRETERMINATED CABLE 72 LC (48MM + 24SM) / 50M

Aginode Ref: 13200649

- Single-mode and multimode fibres in the same cable
- 24/48/72 fibres
- High mechanical resistance
- Supplied with UPSKY™ BOX L/XL connector block

Design

- Small diameter cable
- Dielectric and non-polarized
- UV-resistant
- Waterproof

Installation

- Indoor and outdoor
- LSZH-FR

Environmentally friendly

- Eco-designed
- PEP Eco Passport
- Available upon request



All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

UPSKY™ preterminated cable 72 LC (48MM + 24SM) / 50m

Characteristics

结构特性

颜色	黑
外护套	LSZH-FR (Dca s2 do)
结构类型	Multitube à porteur central
Fibre optic type	SM G657 A2 or OM3
额外加强件	玻璃纱

尺寸特性

近似重量	85 kg/km
光纤数	72
Cable Diameter	8.9 mm

机械特性

机械耐冲击性能	5N.m
耐压	100daN/cm kg/cm
最大牵引力	200daN (80 daN) kN

使用特性

存储温度范围	-40...70 °C
安装类型	室内/户外
Installation temperature, range	0...40 °C