
UPSKY™ preterminated cable singlemode & multimode

UPSKY™ PRETERMINATED CABLE 24 LC (16MM + 8SM) / 100M



Aginode Ref: 13200650

- Single-mode and multimode fibres in the same cable
- 24/48/72 fibres
- Hight mechanical resistance
- Supplied with UPSKY™ BOX L/XL connector block

Design

- Small diameter cable
- Dielectric and non-polarized
- UV-resistant
- Waterproof

Installation

- Indoor and outdoor
- LSZH-FR

Environmentally friendly

- Eco-designed
- PEP Eco Passport
- Available upon request

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

UPSKY™ preterminated cable 24 LC (16MM + 8SM) / 100m

Characteristics

结构特性	
颜色	黑
外护套	LSZH-FR (Dca s2 do)
结构类型	Multitube with central strenght member
Fibre optic type	SM G657 A2 or OM3
额外加强件	玻璃纱
尺寸特性	
近似重量	85 kg/km
光纤数	24
Cable Diameter	8.9 mm
机械特性	
机械耐冲击性能	5N.m
耐压	100daN/cm kg/cm
最大牵引力	200daN (80 daN) kN
使用特性	
最小弯曲半径 - 静态	178 mm
存储温度范围	-40...70 °C
安装类型	室内/户外
Installation temperature, range	0...40 °C
Operating temperature flexing, range	30...60 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.