
LANmark-OF Loose Tube Universal 6 -12 and 24FO - Cca

LANMARK-OF LOOSE TUBE UNIVERSAL 06XMULTIMODE 50/125 OM3 LSZH CCA AQUA



Aginode Ref: N165.LTUN06-AC

- Loose Tube Universal optical fibre cable with high level transmission : OM3
- High fire behavior : reaction to fire Cca according to EN50575:2014+A1:2016
- Indoor/Outdoor cable
- Designed for splicing with pigtails

The new 6FO OM3 Loose Tube technology from Aginode is specifically engineered for indoor building & outdoor where installations where both high performance and fire safety are essential. Designed with a loose tube construction, it offers good protection for fibers against mechanical stresses and environmental factors.

- **CPR (Cca, s2, d1, a1)**: Low fire propagation, reduced smoke emission, minimal toxic gas release.
- **Loose Tube Gel-Filled Design**: Excellent protection against mechanical stress, water ingress, and temperature variations.
- **Vertical installations with loop reserve** for simplified maintenance and future upgrades.
- **Indoor & Outdoor Application:** Ideal for structured cabling in residential, commercial, and public buildings, as well as outdoor environments.
- **High Performance OM3** : Reliable, high-speed data transmission over medium long distances.
- **Flexible and Robust**: Easy to install in ducts, conduits, and technical spaces.
- **UV-Resistant & Waterproof**: Designed to withstand outdoor conditions when required.

The central tube contains till 6 fibers well identified to make installation easy and simple.

STANDARDS

ISO/IEC 11801

Applications

- Building backbone networks
- Data centers
- Outdoor duct installations

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF Loose Tube Universal 06xMultimode 50/125 OM3 LSZH Cca Aqua

Characteristics

结构特性	
结构类型	松套管
光纤类型	OM3 50/125
无卤	IEC 60754-1
护套材料	LSZH Halogen free flame retardant
长度水密封性所用材料	Swellable Glass yarns
尺寸特性	
近似重量	71 kg/km
标称外径	7.6 mm
光纤数	6
管数	1
管径	2.3 mm
机械特性	
耐压(IEC 60794-1-E3)	1500 N/100mm
最大拉力(IEC 60794-1-2-E1)	2000 N
抗拉强度	2000 N
使用特性	
阻燃	IEC 60332-3
阻燃 - 火焰	IEC 60332-1-2
气体腐蚀性	低 IEC 60754-2
Installation temperature, range	-30...60 °C
最小弯曲半径 - 动态	152 mm
最小弯曲半径 - 静态	114 mm
操作温度，范围	-40...70 °C
烟密度	IEC 61034-2
存储温度范围	-40...70 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

抗UV	非常好

DoP: Declaration of Performance

DOP_LANmark-OF Loose Tube Universal 06xMultimode 50/125 OM3 LSZH Cca Aqua.pdf pdf — 59.04 KB 下载

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.