Pre-Connectorized Drop Cable (PCDC)

FIGURE 8 WITH MESSENGER (STEEL WIRE) - ADSS 1FO - HQ



Aginode Ref: PCDCLHQ00xxxx - SP2068

Connectorization:

- Hardened Quarter Turn*

**Aginode Hardened Quarter Turn PCDC are fully compatible with Huawei FastConnect.*

Lengths (in m) and packaging available:

- Up to 500m
- Individual recyclable paper bag
- Individual recyclable cardbord box. With spool of durable cardboard for long lengths

Description


This cable is designed for subscriber connections in terminal part. It's suitable for aerial installation.

Characteristics & Applications

- Aerial applications (max. distance between poles 80m.)
- Suitable for hardened pre-connectorization

Construction

- Strength members: 2x steel wire
- Messenger wire: 1x steel wire
- Outer sheath: Black LSZH



STANDARDS

IEC 60794

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Figure 8 with messenger (steel wire) - ADSS 1FO - HQ

Characteristics

结构特性	
颜色	黑
绝缘	是
光纤类型	SM (G657.A2)
纵向防水	Yes
外护套	低烟无卤
电缆类型	Aerial
尺寸特性	
近似重量	20 kg/km
Cable Diameter	2.0±0.1 × 5.2±0.2 mm
光纤数	1
光纤数，范围	...
传输特性	
最大插入损耗，dB	0.25 dB
插入损耗，典型值	0.12 dB
最小回波损耗，dB	65 dB
使用特性	
应用类型	Customer connection
Installation temperature, range	-30...70 °C
安装类型	架空 - 自承式
最小弯曲半径 - 工作	20mm mm

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.