

Pre-Connectorized Drop Cable (PCDC)

FIGURE 8 WITH MESSENGER (STEEL WIRE) - ADSS 1FO - HQ

Aginode Ref: PCDCLHQ00xxxx - SP2068

Connectorization:

- Hardened Quarter Turn*

*Aginode Hardened Quarter Turn PCDC are fully compatible with Huawei FastConnect.

Lengths (in m) and packaging available:

- Up to 500m
- Individual recyclable paper bag
- Individual recyclable cardboard box. With spool of durable cardboard for long lengths

Description


This cable is designed for subscriber connections in terminal part. It's suitable for aerial installation.

Characteristics & Applications

- Aerial applications (max. distance between poles 80m.)
- Suitable for hardened pre-connectorization

Construction

- Strength members: 2x steel wire
- Messenger wire: 1x steel wire
- Outer sheath: Black LSZH



STANDARDS

IEC 60794

Figure 8 with messenger (steel wire) - ADSS 1FO - HQ

Characteristics

结构特性

颜色	黑
绝缘	是
光纤类型	SM (G657.A2)
纵向防水	Yes
外护套	低烟无卤
电缆类型	Aerial

尺寸特性

近似重量	20 kg/km
Cable Diameter	$2.0 \pm 0.1 \times 5.2 \pm 0.2$ mm
光纤数	1
光纤数, 范围	...

传输特性

最大插入损耗, dB	0.25 dB
插入损耗, 典型值	0.12 dB
最小回波损耗, dB	65 dB

使用特性

应用类型	Customer connection
Installation temperature, range	-30...70 °C
安装类型	架空 - 自承式
最小弯曲半径 - 工作	20mm mm