

LANmark-OF Loose Tube Universal 48 - 72 - 96 & 144FO - Cca

LANMARK-OF LOOSE TUBE UNIVERSAL 96XMULTIMODE 50/125 OM4 LSZH CCA VIOLET

Aginode Ref: N167.LTUN96-VC

- Loose Tube Universal optical fibre cable with high-level transmission: OM4
- High fire performance: Reaction to fire Cca according to EN50575:2014+A1:2016
- Indoor/Outdoor cable
- Designed for splicing with pigtails

The new **96FO OM4 Loose Tube technology** from Aginode is specifically engineered for indoor buildings & outdoor where installations require both high performance and fire safety. Designed with a loose tube construction, it offers excellent protection for fibers against mechanical stresses and environmental factors.

- **CPR (Cca s1a, d1, a1):** Low fire propagation, reduced smoke emission, and minimal toxic gas release.
- **Loose Tube Construction:** Excellent fiber protection against mechanical stress and temperature variations.
- **Indoor & Outdoor installation :** Ideal for structured cabling in residential, commercial, and public buildings, with environmental resistance for exposed sections.
- **High Performance OM4:** Reliable, high-speed data transmission over long distances.
- **Flexible and Robust**
- **UV-Resistant & Waterproof:** Designed to withstand outdoor conditions when required.

The central tube contains up to 96 fibers organized in 8 bundles of 12 fibers, each clearly identified to simplify installation.

Applications:

- Building backbone networks
- Data centers
- Outdoor installations



STANDARDS

ISO/IEC 11801

LANmark-OF Loose Tube Universal 96xMultimode 50/125 OM4 LSZH Cca Violet

Characteristics

结构特性

结构类型	松套管
光纤类型	OM4 50/125
无卤	IEC 60754-2
长度水密封性所用材料	Jelly
不含金属	Yes
外护套	低烟无卤

尺寸特性

近似重量	145 kg/km
标称外径	11.8 mm
光纤数	96
管数	8

机械特性

耐挤压 (IEC 794-1-E3)	2000/10 N/cm
最大拉力(IEC 60794-1-2-E1)	1800 N
抗冲击性能(IEC 60794-1-E4)	20 N·m
额定长期抗拉强度	0.6 kN

使用特性

阻燃 - 火焰	IEC 60332-3-24
Installation temperature, range	-20...60 °C
安装类型	室内/户外
最小弯曲半径 - 动态	236 mm
最小弯曲半径 - 静态	118 mm
操作温度, 范围	-40...70 °C
烟密度	IEC 61034-2
存储温度范围	-30...60 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

抗UV

非常好

DoP: Declaration of Performance

DOP_LTUN_96XSM OM4_Cca.pdf pdf — 59.07 KB [下载 ↓](#)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.