

Pre-Connectorized Drop Cable (PCDC)

AERIAL AND DUCT CABLE 5.0MM - PIA

Aginode Ref: PCDCIxxxx - SP2065

This outdoor cable is suitable for duct and aerial installation, featuring a jelly-filled loose tube with 1 fibre, dry water-blocking materials, and an HDPE sheath reinforced with two embedded FRP rods.

This cable is designed for outdoor duct and aerial installations. It features a loose tube construction containing 1 fibre, filled with jelly for fibre protection. The cable includes water-blocking materials to prevent moisture ingress. Its outer sheath is made of high-density polyethylene (HDPE) and includes two fibre-reinforced plastic (FRP) elements embedded symmetrically in the sheath for added strength and stability.

Breaking load: max 2000N

PIA Approved



STANDARDS

IEC 60794
IEC 60793

Test Methods

All optical measurements at 1550 nm

Test	Conditions	Acceptance criteria
Tension Loading IEC 60794-1-2 E1	Tensile strength: 800N and 300N Sample length: ≥ 50 m, 1 min	$\Delta\alpha \leq 0.1$ dB under 300N and reversible under 800N
Crush/Compression IEC 60794-1-2 E3	Crush: 20Kg/cm, 1min Number of tests: 3, at least 20cm apart.	$\Delta\alpha$ reversible No damage
Impact IEC 60794-1-2 E4	Impact energy: 5Nm, R=300mm number of test: 3	$\Delta\alpha$ reversible
Torsion IEC 60794-1-2 E7	1m, $\pm 180^\circ$, 10 cycles	$\Delta\alpha \leq 0.1$ dB
Bending IEC 60794-1-2 E11	R=10xCable Φ , 4 turn, 3 cycles	$\Delta\alpha$ reversible
Temperature Cycling IEC 60794-1-2 F1	-20~+70°C, two cycles, t1=180min	$\Delta\alpha \leq 0.1$ dB
Water penetration IEC 60794-1-2 F5B	Height of water column: 1m Sample length: 3m, 24h	No water leakage

Aerial and duct cable 5.0mm - PIA

Characteristics

结构特性

颜色	黑
连接器类型	Hardened Standard (Corning Optitap compatible)
绝缘	是
光纤类型	SM (G657.A2)
外护套	HDPE
电缆类型	Aerial

尺寸特性

近似重量	20 kg/km
Cable Diameter	5.0 mm
光纤数	1

机械特性

断裂强度	Max 2 kN
耐压	20 kg/cm
最大拉力	800 N

传输特性

最大插入损耗, dB	0.25 dB
插入损耗, 典型值	0.12 dB
最小回波损耗, dB	65 dB

使用特性

应用类型	Customer connection
Installation temperature, range	-5...50 (operation -20...70) °C
安装类型	架空 - 自承式
最小弯曲半径 - 工作	R=10D without tension mm
包装	PCDC packaging

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.