

LANmark-OF UC PE (单元管钢装甲)

LANMARK-OF UC 6X MULTIMODE 50/125 OM4 PE BLACK

Aginode Ref: N167.UCPE06B

UC optical fibre cables

- Outdoor in ducts or direct burial
- Corrugated steel tape armour
- Available in all fibres grades
- Provides full rodent protection


Description and Application

The construction is suitable for use outdoor in ducts and for direct burial. It consists of a corrugated steel tape armouring providing full rodent protection. It is surrounded by glass yarns. The cable has a HDPE outer jacket.

The loose tube design has a capacity of up to 24 fibres.

Diameter of the fibres is 255 um. Termination of these fibres is done with splicing of pigtails.

The cable is watertight due to the gel in the loose tube and the watertight glass yarns.



STANDARDS

ISO/IEC 11801

LANmark-OF UC 6x Multimode 50/125 OM4 PE Black

Characteristics

结构特性

| | |
|------------|----------------------------------|
| 结构类型 | 松套管 |
| 光纤类型 | OM4 50/125 |
| 无卤 | 是 |
| 护套材料 | Polybutylene Terephthalate (PBT) |
| 长度水密封性所用材料 | Swellable Glass yarns |

尺寸特性

| | |
|------|----------|
| 近似重量 | 64 kg/km |
| 标称外径 | 7.6 mm |
| 光纤数 | 6 |
| 管数 | 1 |
| 管径 | 2.8 mm |

机械特性

| | |
|--------------------|--------------|
| 耐压(IEC 60794-1-E3) | 2000 N/100mm |
| 抗拉强度 | 1500 N |

使用特性

| | |
|---------------------------------|-------------|
| Installation temperature, range | -30...70 °C |
| 操作温度, 范围 | -40...70 °C |
| 烟密度 | IEC 61034-2 |
| 存储温度范围 | -40...70 °C |
| 抗UV | 非常好 |

DoP : Declaration of Performance

DOP_UC 6xMM50 OM4 BK.pdf pdf — 58.99 KB [下载](#) ↓