LIGHTDROP

LIGHTDROP SPLICE 08







All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Aginode Ref: LDSFSP08HQNANA04SD00NASTNANANA


Featuring:

- 8 Hardened Quarter Turn (FastConnect compatible) bottom ports.
- 48 fibres splicing capacity.
- 1 oval optical cable entry up to 16mm.
- 2 branch optical cable entries and up to 14mm.
- Integration of optical splitters (i.e. 4 splitters 1:2 or 2:2).
- Other splice trays and optical splitter configurations available.
- Mounting bracket options for overlenght cable storage.

Terminal max. attenuation*:

Splitter ratio	Output
1:2	4.20 dB
2:2	4.70 dB

*Total terminal attenuation, including insertion losses from pre-connectorization.



All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LIGHTDROP SPLICE 08

Characteristics

结构特性	
颜色	黑
材料	PP
机械特性	
IK Rating	8
使用特性	
安装类型	户外
操作温度，范围	-40...65 °C
包装	箱
RoHS compliant	Yes
抗UV	是
防水	IP 68



PDF - 962.79 KB
Notice LIGHTDROP SPLICE
下载

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.