

DCmark Rack Unit Solution Server DC

DCMARK RACK UNIT SOLUTION SERVER DC 42U 800X800

Aginode Ref: NRCK.420808440-B

The DCmark RUS NRCK.420808440-B is a high-performance server rack engineered for optimal airflow thanks to his high perforation ration at 80%. With the need of IA and GPU server more and more heavy, the DCmark rack metallic frame is designed to support high loading capacity :

- Loading capacity up to 1500kg to support heavy server
- Perforation ratio at 80% to offer a perfect air flow
- Double doors for a better access
- Lateral cable manager to ensure easy cable management and high reliability
- optional : rear support for intelligent PDU and internal lateral cable tray

The NRCK.420808440-B, offer a height of 42U with a depth of 800mm and width of 800mm

The DCmark RUS NRCK.420808440-B is a high-performance server rack engineered for optimal airflow thanks to his high perforation ration at 80%. With the need of IA and GPU server more and more heavy, the DCmark rack metallic frame is designed to support high loading capacity up to 1500kg.

Equipped with several features and smart cable management, DCmark Rack Unit Solution will ensure reliability, easy installation & easy maintenance for DC technician. The cable management will ensure good cable management and ensure perfect bending radius for cable and patch cord in order to offer the best performance especially for fiber optical cable.

The double front door will offer a full access to the cabling in order to facilitate all technical intevention inside the rack. The doors are equipped with a 3 locking point system closing to ensure high security level. Smart handle with RFDI card can be also installed to avoid key management.

The NRCK.420808440-B, offer a height of 42U with a depth of 800mm and width of 800mm



DCmark Rack Unit Solution Server DC 42U 800x800

Characteristics

结构特性

柜式		19"
电缆引入线	From the top through brush panel and from bottom through sliding access	
Cabling management	Lateral front cable manager	
颜色		黑
材料		钢
机架版本		Server
Type of front door		double perforated at 80%
Type of rear door		double perforated at 80%

尺寸特性

19" mounting		front & rear
近似净重量		114 kg
深度		800 mm
高度		2017 mm
高度单位		42 U
宽度		800 m

机械特性

IK Rating		07
-----------	--	----

使用特性

Locking system	3 locking points with mechanical handle	
包装		carton