
DCmark Rack Unit Solution Server DC

DCMARK RACK UNIT SOLUTION SERVER DC 42U 800X800





Aginode Ref: NRCK.420808440-B

The DCmark RUS NRCK.420808440-B is a high-performance server rack engineered for optimal airflow thanks to his high perforation ration at 80%. With the need of IA and GPU server more and more heavy, the DCmark rack metallic frame is designed to support high loading capacity :

- Loading capacity up to 1500kg to support heavy server
- Perforation ratio at 80% to offer a perfect air flow
- Double doors for a better access
- Lateral cable manager to ensure easy cable management and high reliability
- optional : rear support for intelligent PDU and internal lateral cable tray

The NRCK.420808440-B, offer a height of 42U with a depth of 800mm and width of 800mm

The DCmark RUS NRCK.420808440-B is a high-performance server rack engineered for optimal airflow thanks to his high perforation ration at 80%. With the need of IA and GPU server more and more heavy, the DCmark rack metallic frame is designed to support high loading capacity up to 1500kg.

Equipped with several features and smart cable management, DCmark Rack Unit Solution will ensure reliability, easy installation & easy maintenance for DC technician. The cable management will ensure good cable management and ensure perfect bending radius for cable and patch cord in order to offer the best performance especially for fiber optical cable.

The double front door will offer a full access to the cabling in order to facilitate all technical intevention inside the rack. The doors are equipped with a 3 locking point system closing to ensure high security level. Smart handle with RFDI card can be also installed to avoid key management.

The NRCK.420808440-B, offer a height of 42U with a depth of 800mm and width of 800mm

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

DCmark Rack Unit Solution Server DC 42U 800x800

Characteristics

结构特性	
柜式	19"
Cabling management	Gestion de câble latérale
颜色	黑
电缆引入线	Entrée supérieure via passe-fil balai et accès par la base
材料	钢
机架版本	Server
Type of front door	Double porte AV perforée
Type of rear door	Double porte AR perforée
尺寸特性	
19'' mounting	Avant & Arrière
高度	2017 mm
宽度	800 m
近似净重量	114 kg
深度	800 mm
高度单位	42 U
机械特性	
IK Rating	07
使用特性	
包装	carton
Locking system	3 points de fermeture avec poigné

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.