

# DCmark Rack Unit Solution Collocation DC

## DCMARK RACK UNIT SOLUTION COLLOCATION DC 42U 2 COMPARTMENTS

**Aginode Ref:** NRL2.420808340-B

DCmark RUS-Collocation DC rack is designed to maximize security, flexibility, and efficient space utilization in shared data center environments. Their reinforced structure and advanced access control options ensure reliable isolation between tenants. Engineered for seamless integration, clean cabling, and scalable growth.

Rack are equipped with 2 compartment of 20U; each have a single front perforated door, lockable by key. Each key have a specific number for the confidentiality.

Cable entries with brush panel equipped the roof and serve the different compartment through closed cable ducts to offer a high level of security and avoid having access to the cable to all the tenants.

DCmark RUS-Collocation DC rack is designed to maximize security, flexibility, and efficient space utilization in shared data center environments. Their reinforced structure and advanced access control options ensure reliable isolation between tenants. Engineered for seamless integration, clean cabling, and scalable growth.

The Rack NRCL2 is equipped with 2 compartments of 20U with a total loading capacity of 1500Kg. Each compartment have a single front perforated door and double rear perforated door.

To ensure a high confidentiality of the tenant, each compartment have is own key with a specific number printed on the barrel (Aginode is the only part knowing the correspondance between this code and the key number).

Cable entries with brush panel equipped the roof and serve the different compartment through closed cable ducts to offer a high level of security and avoid having access to the cable to all the tenants.



# DCmark Rack Unit Solution Collocation DC 42U 2 compartments

## Characteristics

### 结构特性

柜式	19"
电缆引入线	from the top through brush panel and closed duct
颜色	黑
Compartment number	2x20U
材料	钢
机架版本	Collocation
Type of front door	Single perforated door 80%
Type of rear door	double perforated at 80%

### 尺寸特性

19" mounting	front & rear
近似净重量	128 kg
Compartment Height U	20U
深度	800 mm
高度	2017 mm
高度单位	42 U
宽度	800 m

### 机械特性

IK Rating	07
-----------	----

### 使用特性

IP等级	IP20
Key type	specific number
Locking system	Individual key per compartment

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.