

essential-OF 固定式配线架 SP（精选套装）版本

ESSENTIAL-OF 1U 24口固定式光纤配线架，含24个双工LC适配器和48根G652D单模尾纤，附带安装和熔接配件，黑色

Aginode Ref: N441.4SPL48

- 配备标准适配器的1U固定式配线架，兼容性广泛
- 最多支持 24 个单工 SC 或双工 LC 适配器
- 开箱即用配置，配备24个双工LC适配器和48根G652D单模尾纤
- 随附所有配件，如熔接套件和安装螺丝套件。
- 后端锁扣设计便于拆卸上盖板
- 每个端口上方均印有白色丝印标签
- 适用于19英寸机柜和机架安装

Aginode 推出的 essential-OF 固定式配线架 SP（精选套装）版本，操作简单便捷，从而带来更佳的客户体验。Aginode essential-OF 固定式配线架的典型应用场景包括办公室、校园及小型数据中心的骨干网络，在提供所需密度同时，还兼具简便性和灵活性。

该配线架采用双工LC或单工SC标准适配器设计，并随附跳线和配件。

SP（精选套装）版本涵盖了最常见的配置，便于现场快速部署。具体特性请参阅详细说明。

多根电缆可通过扎带固定在托盘后部，后端设有 4 个直径为 20 毫米的插槽。

该固定式配线架适用于 19 英寸机柜和机架安装，表面采用全黑磨砂喷墨涂层。



STANDARDS

ANSI/TIA-568.3-D
ISO/IEC 11801

essential-OF 1U 24口固定式光纤配线架，含24个双工LC适配器和48根G652D单模尾纤，附带安装和熔接配件，黑色

Characteristics

结构特性

Fibre Type Connector	LC/UPC
光纤类型	SM (G.652)

尺寸特性

宽度	19 inches
深度	235 mm
高度单位	1 U

使用特性

适配器	Duplex LC SM Blue
-----	-------------------

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

